TYPE K
TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04 *ISO-9001, CE, IEC1010*

TP-01

TP-02A

TP-03

TP-04

LUTRON ELECTRONIC

The Art of Measurement

TYPE K TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04

Type K PROBE Model	***Measurement R$ange***	***Accuracy***
(Type K) TP-01	* Max. short-tern operating Temperature: 300 ℃ (572 ℉). * It is an ultra fast response naked-bead thermocouple suitable for many general purpose application.	± 0.4 %
Thermocouple Probe (Type K), TP-02A	* Measure Range: -50 ℃ to 900 ℃, -50 ℉ to 1650 ℉. * Dimension:10cm tube, 3.2mm Dia.	± 0.75 %
Thermocouple Probe (Type K), TP-03	* Measure Range: -50 ℃ to 1200 ℃, -50 ℉ to 2200 ℉. * Dimension: 10cm tube, 8mm Dia.	± 0.4 %
Surface Probe (Type K), TP-04	* Measure Range: -50 ℃ to 400 ℃, -50 ℉ to 752 ℉. * Size : Temp. sensing head - 15 mm Dia. Probe length - 120 mm.	± (0.75 % +0.5 ℃)

* Appearance and specifications listed in this brochure are subject to change without notice.