



EVX series

EVX 12300 12V 30AH

Valve Regulated Lead Acid Battery

Maintenance-Free Sealed Lead Acid Battery.

Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99%.

Design for Cyclic Applications

【Design Life】

400 cycles @ 100%DOD at 25°C

1800 cycles @ 30%DOD at 25°C

【Operating Temperature Range】

Nominal Operating Temperature : 25°C (77°F)

Discharge : -15°C ~ 50°C (5°F~122°F)

Charge: -15°C ~ 40°C (5°F~104°F)

Storage: -15°C ~ 40°C (5°F~104°F)

【Equalization Charging Voltage】

14.4 ~ 15.0 VDC/Unit at 25°C (77°F)


【Self Discharge】

Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F);

Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).

Specification

Nominal Voltage	12V (6 cells per unit)		
Nominal Capacity	30 AH @20HR-rate to 1.75V per PCS @25°C (77°F)		
Weight	Approx. 10.40 Kg (22.92 lbs)		
Maximum Discharge Current	400A (5sec)		
Internal Resistance	Approx. 7.9 mΩ		
Short Circuit Current	--		
Maximum Charge Current	9.00A		
Terminal types	I1 terminal to accept M5 bolt		
Terminal hardware Torque	59 Kgf-cm / 51 lbf-in / 5.73 N-m		
Container Material	ABS (UL 94-HB) & Flame Retardant (94-V0) available upon request		
Dimensions	Length (L)	166.0±2.0 mm	6.54±0.08 inch
	Width (W)	125.0±1.5 mm	4.92±0.06 inch
	Container Height (h)	175.0±2.0 mm	6.89±0.08 inch
	Overall Height (H)	175.0±2.0 mm	6.89±0.08 inch



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.67V	31.2	22.4	17.7	12.7	10.3	7.48	6.05	5.03	4.32	3.39	2.82	1.61
1.70V	30.6	21.9	17.3	12.3	9.94	7.26	5.87	4.90	4.20	3.29	2.75	1.58
1.75V	30.0	21.4	16.8	11.9	9.66	7.04	5.70	4.76	4.09	3.21	2.68	1.54
1.80V	29.2	20.8	16.3	11.6	9.38	6.83	5.54	4.64	3.98	3.12	2.61	1.50
1.83V	28.4	20.2	15.8	11.3	9.07	6.61	5.37	4.51	3.87	3.04	2.53	1.45
1.85V	27.6	19.5	15.3	10.9	8.79	6.40	5.21	4.39	3.76	2.94	2.46	1.41

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)

F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.67V	374	268	212	152	123	89.8	72.6	60.4	51.5	40.1	33.1	17.3
1.70V	367	263	207	147	120	87.1	70.4	58.6	50.1	39.1	32.2	16.8
1.75V	359	256	202	143	116	84.5	68.4	57.1	48.8	38.1	31.4	16.4
1.80V	351	250	196	139	112	81.9	66.4	55.6	47.5	37.0	30.5	15.9
1.83V	341	242	190	135	109	79.3	64.4	54.1	46.1	35.9	29.5	15.4
1.85V	332	235	184	131	105	76.7	62.4	52.6	44.8	34.7	28.4	14.9

Please refer to the official site for the latest rating confirmation. URL: www.csb-battery.com

Issued: 161101

Sales Offices

日立化成能源科技股份有限公司
Hitachi Chemical Energy Technology Co., Ltd.

BUSINESS HEADQUARTERS

Tel: +886-2-2880-5600

Fax: +866-2-2888-3300

USA OFFICE

Tel: +1-817-244-7777 / 1-(800)3-CSB-USA (272872)

Fax: +1-817-244-4445

SHENZHEN OFFICE (CHINA)

Tel: +86-755-8831-6488, 8831-6775

Fax: +86-755-8831-6075

EUROPE (EMEA) OFFICE

Tel: +31(0)180-418-140

Fax: +31(0)180-418-327

SHANGHAI OFFICE (CHINA)

Tel: +86-21-5046-1622, 5046-0833

Fax: +86-21-5046-1046

TAIPEI OFFICE

Tel: +886-2-2880-5600

Fax: +866-2-2888-3300

BEIJING OFFICE (CHINA)

Tel: +86-10-5820-5336, 5820-5338

Fax: +86-10-5820-3053

Recognized under UL 1989,
and certified by ISO 9001, 14001.

