

Inrush current (366)

True RMS (363/366)



Model 360



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031

The 360 series clamp meters offer all needed features for measurement. It with small bodies and jaws design for perfectly handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display. Measuring starting current for motors, lighting, etc. is easy with the inrush current function (366 only).

- Double molded plastic housing
- Inrush current function (366 only)
- Auto Power Off

Features	360	361	362	363	366
Current measurement	AC	AC	AC/DC	AC/DC	AC/DC
Max. Resolution	1mA	1mA	10mA	10mA	10mA
LCD display counts	2000	4000	4000	4000	6000
AC True RMS				*	*
Display with backlight	*	*	*	*	*
Data Hold	*	*	*	*	*
Max Hold	*				
Zero Function			*	*	*
Auto Power Off	*	*	*	*	*
Low battery indication	*	*	*	*	*
Peak Current				*	
Inrush Current					*
1.2" (30mm) Jaw opening	*	*	*	*	*

Specifications			360	361	362	363	366
Function	Max Range	Basic Accuracy					
Voltage DC	600V	±(0.5%+1d)	*	*	*	*	*
Voltage AC	600V	±(1.5%+2d)	*	*	*	*	*
Current DC	400A	±(2.0%+5d)			*	*	600A
Current AC	400A	±(2.5%+4d)	*	*	*	*	*
Resistance	40MΩ	±(3.0%+5d)	20MΩ	*	*	*	60MΩ
Temperature	1000°C/ 1832°F	±(3.0%+3d)		*	*	*	*
Capacitance	100uF	±(2.5%+5d)			*	40mF	60mF
Frequency	10MHz	±(1.2%+2d)			*	*	*
Inrush Current	600A	±(1.5%+2d)					*
Continuity check	Buzzer sounds at 50Ω		*	*	*	*	*
Diode test	Test current 0.3mA		*	*	*	*	*



Model 362



Model 363



Size(HxWxD): 197mm x 70mm x 40mm

Weight: 183g

Accessories:

Test leads, gift box with carrying case, Temperature probe(361,362, 363, 366 only) and 9V battery.