



## FLIR MR40

### Moisture Pen + Flashlight

The FLIR MR40 is a pocket-portable, rugged 2-pin, single-scale moisture meter with an integrated flashlight for wood and common building materials – ideal for builders, building inspectors, remodelers, moisture remediation technicians, pest control professionals, and residential roofing and flooring contractors. Providing reliable and accurate measurements offered at a highly affordable price point, MR40 is a quick and easy-to-use tool to find and quantify moisture content.

When used in combination with a thermal camera, MR40 can help confirm whether a cold spot in a thermal image is moisture, and measure the severity of the problem.



Integrated worklight eliminates the need to carry a separate flashlight



Rugged, compact design for measurements in tight spaces

### Easy to use

*Simple and effective tool for reliable measurements*

- Clear LCD display
- Simple On/Off button with 'Auto Power Off'
- Replaceable pins (includes 2nd set)
- Audible indication of measured range (5- 12%, 13- 60%, 60%+)

### Convenient, portable, rugged design

*Ready to work when and wherever you are*

- Small enough to carry in your pocket and take measurements in tight spaces
- IP54 splash-proof rated, operating temperature: -10°C to 50°C
- 3-meter drop tested

### Reliable and accurate measurements

*Provides essential features and functions to quickly verify and quantify moisture*

- Measurement 'Hold' function
- Calibration/Pin check integrated in cap

## Specifications

Measurements	
Measurement Range	5% to 60% MC (Moisture Content)
Measurement Accuracy	5 to 30% MC (Moisture Content): +/- 2% 30 to 60% MC (Moisture Content): Reference only  Note: For materials other than Group 9/Building Materials: plywood, drywall, and oriented strand board (OSB), download the MR40 Material Conversion Table (publication MR40-AN01): <a href="http://tinyurl.com/jteb653">http://tinyurl.com/jteb653</a>
Audible Indication	5 to 12%: Low Beep rate. 13 to 60%: Higher beep rate. More than 60%: Highest Beep rate (Display OL)
Calibration/ Pin Check, Integrated in Cap	16%
General Information	
Flashlight	~40 lumens
Display	LCD
Electrode pins	Integrated, Replaceable (4 pins included)
Measurement Principle	Electrical Resistance
Warranty	Limited lifetime
Calibration cycle	N/A
Battery type	2 x AAA alkaline batteries (included)
Battery life	70 Hrs W/O Flashlight
Battery status indicator	4 Bar battery icon
Auto Power Off (APO)	3 minutes
Drop test	3 m
IP Rating	IP54 Splash Proof
Operating temperature	-10 to 60°C
Weight	80g (2.8 oz) with batteries
Dimensions (H x W x L)	193 x 26 x 31 mm
Material	PC-ABS w/TPE Overmold

What's in the Box	UPC
MR40 Moisture Pen + Flashlight (spare set of pins in box)	793950370414
Accessories Optional	
MO25-PINS Spare electrode pins (10 pins per pack)	793950470268

Specifications are subject to change without notice. For the most up-to-date specifications, go to [www.flir.com](http://www.flir.com)



Quick and easy to use; reliable and accurate results



Use MR40 to confirm whether the cold spot found in a thermal image is moisture



**SWEDEN**  
Instruments Division  
FLIR Systems AB  
Antennvägen 6  
187 66 Täby  
Tel. : +46 (0)8 753 25 00  
E-mail : [flir@flir.com](mailto:flir@flir.com)

**FLIR UK**  
West Malling  
Tel. +44 (0)1732 220 011

**FLIR Spain**  
Madrid  
Tel. +34 91 573 48 27

**Benelux**  
Sales Administration  
FLIR Commercial Systems  
Luxemburgstraat 2  
2321 Meer  
Belgium  
Tel.: +32 (0) 3665 5100

**FLIR Russia**  
Moscow  
Tel. + 7 495 669 70 72

**FLIR Middle East**  
Dubai  
Tel. +971 4 299 6898

**FLIR Germany**  
Frankfurt  
Tel. +49 (0)69 95 00 900

**FLIR Turkey**  
Istanbul  
Tel. +90 (212) 317 90 55

**FLIR France**  
Torcy  
Tel. +33 (0)1 60 37 01 00

**FLIR Africa**  
Johannesburg  
Tel. +27 11 300 5622

**FLIR Italy**  
Milan  
Tel. +39 (0)2 99 45 10 71

[www.flir.com](http://www.flir.com)  
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. [Updated Mar 7] 17-0533\_EMEA