



This high-definition video borescope has 2.4 "TFT LCD, Resolution: 480 (W) X234 (H), applying H.264 video codec technology makes images clear and exquisite, and equipped with curved waterproof goose-shaped tube which is a meter long, it will be easy to detect the object that cannot be touched and can't be visible by naked eye, meanwhile, access to AV video display and the signal system can be derived in both NTSC / PAL formats and can switch the signal format automatically.

- Can be applied to detect whether the internal components of equipments, that human eye can't see, are working properly (Such as cars, large machinery)
- Can check the objects underwater when you put the camera in water (Drainage works)
- Can be used in some special monitoring places, under the cars etc
- Any place where visual access is a problem.



# BS-128 Video Borescope



## **Technical Specifications**

| Camera                            |                   |
|-----------------------------------|-------------------|
| Sensor size                       | 1/4 inch CMOS     |
| Sensor pixel                      | 300,000           |
| Maximum resolution                | 640 x 480         |
| Maximum frame rate(FPS)           | 30FPS/S           |
| Depth of Field (DOF)              | 10mm ~∞(infinity) |
| Gooseneck length                  | 1m(39")           |
| Camera diameter                   | 17mm(0.66")       |
| TFT-LCD Display                   |                   |
| Color TFT-LCD size                | 2.4 inch          |
| Display Resolution                | 480 (W)X 234 (H)  |
| Active area                       | 48mmX 35.6mm      |
| Light Source                      |                   |
| 4pcs highlighted LED              |                   |
| Video Format                      | NTSC / PAL        |
| Standard Automatic Conversion     |                   |
| Power                             |                   |
| Battery                           | 4X"AA"            |
| Working Current                   | MAX 300mA         |
| Low battery indication            | 4.8V±0.2V         |
| Tomporaturo                       |                   |
| Temperature Operating Temperature | 0°C - 50°C        |
|                                   | -20°C - 60°C      |
| Storage temperature               | 5% - 85%          |
| Relative Humidity                 | 5% - 85%          |

## Accessories

Battery, Carrying Case, Mirror, Hook, Magnet, Instruction Manual and Test Certificate.

## Contact :



#### **CEM INSTRUMENTS (INDIA) PVT. LTD.**

32A, Ganesh Chandra Avenue, 4th Floor, Kolkata-700013 Tel: 033-22151376, 22159759

Email: info@cem-instrumets.in / info@cem-india.com Web: www.cem-instruments.in / www.cem-india.com

#### **CEM INSTRUMENTS HEADQUATER & FACTORY**

19th Building, 5th Region, Baiwangxin Industry Park, Songbai Road, Baimang, Xili, Nanshan, Shenzhen, China, 518108

Tel: +86-755-27353188, Fax: +86-755-27653699