

**FEATURES:**

- 4-20 mA with 1  $\mu$ A resolution
- Basic Accuracy 0.025% + 5 $\mu$ A
- Auto-Ramp and Easy Step Functions
- 1-100% Input
- 0-20mA, 0-24mA Selectable
- 0-24V Output

**ELECTRICAL SPECIFICATIONS:**

RANGE	RESOLUTION	Accuracy
0-4mA	0.001mA	$\pm 0.025\% \pm 10\mu\text{A}$
4-20mA	0.001mA	$\pm 0.025\% \pm 5\mu\text{A}$
20-24mA	0.001mA	$\pm 0.025\% \pm 5\mu\text{A}$
0-4V	0.001V	$\pm 0.05\% \pm 10\text{mV}$
4-20V	0.001V	$\pm 0.05\% \pm 5\text{mV}$
20-24V	0.001V	$\pm 0.05\% \pm 5\text{mV}$

**GENERAL SPECIFICATIONS:**

**Battery Type:** 9V Alkaline Battery (External Power Input 9-15V)

**Display:** 4+5 Digits

**Operating Temperature:** 0 to 50°C (32 to 122°F)

**Operating Humidity:** Less than 85% relative

**Storage Temperature:** -20 to 60°C (-4 to 140°F)

**Dimension:** 88×168×26mm

**Weight:** 330g

**Accessories:** Carrying case, Users Manual, 6×1.5V AA batteries, External Battery Pack, Alligator clip.