

MINI DIGITAL CLAMP METER

KPS-PA420 MINI



- Current clamp
- Ø28 mm maxilla
- 2000 counts
- AC / DC voltage, AC current and resistance measurements
- Continuity warning and diode test
- Read hold
- Low battery indicator
- CAT.III 600V according to EN 61010

KPS-PA420 MINI

MINI DIGITAL CLAMP METER

General	
Power Supply	3×1.5V AAA Batteries
Product Size	198mm × 79mm × 38mm
Product Weight	195g
Certificate	CE/ETL/RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	2000
Jaw Opening	Φ28mm/1.1"
Diode	4,5V
Continuity Buzzer	<70Ω
Data Hold	✓
Low Battery Display	✓

KPS-PA420 MINI

MINI DIGITAL CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	600V	1V	± (1.0% + 3 dígitos)
AC Voltage	600V	1V	± (1.5% + 10 dígitos)
AC Current	2A/20A	1mA/10mA	± (2.0% + 10 dígitos)
	400A	1A	± (2.0% + 5 dígitos)
Resistance	2kΩ	1Ω	± (1.0% + 5 dígitos)

Product Code Information

SKU	KPSPA420MINICBINT
EAN code	8435394747194
UPC code	810053670149
Pcs/export carton	20